

HZHX-Y



HZHX-Y

2024





服务宗旨：快速响应，**客户满意，超过期望**

- [illegible]

	2	2
--	---	---

)





HZHX-Y

3.5

“ X Y ”

160m 10V 550kV 35kV
35kV

DC 3.7V USB 10

315MHz 433MHz
160m

3.5

AC 10V 550kV

0.0 ° 360.0 °

45Hz 75Hz

0.1 ° 0.1Hz

(23 ± 5 80%RH) ≤ ± 10 °

≤ ± 2Hz

: 30 ° 30 ° : 90 ° 150 ° 210 ° 270 °

X

Y

3 0.6 ()

9999

35kV 110kV (

)

35kV 110kV ()

“ -- -- ”



2 /

145mm × 60mm × 48mm

250mm × 100mm × 40mm

HOLD

HOLD

ESC

ENTER

“ ---- ”

15

3.2V

35mA max

300mA max

205g()

395g()

1kg

5.4kg()

-10 40 80%Rh

-10 60 70%Rh

433MHz 315MHz

AC 110kV/rms(5)

2000V/rms()

2000V/rms()

IP63

GB13398 92 GB311.1 311.6 8 3DL408 91

1kV 35kV

DL/T971-2005

IEC61481 A2:2004 IEC 61243 1 ed.2:2003

可靠，轻便易用

列满意，超过期

+1 -1 +10 -10 +100 -100

027-83267669

ezi.com

ezi@163.com





1

3.2V

4

2

4

3

POWER

2

4

“

”

“

”

1

2

1.

2.



1

2

3

2

24

027-83267669

24

48

4

